







#### **Description**

Color:

Dimming:

The LITĒLUME™ Sconce Modern Series (LL–SWS) luminaire incorporates a traditional fresh design. Features a die-formed cold rolled steel housing in Satin Nickel (SN) or oil rubbed bronze (ORB) with frosted glass lens for a subtle approach. Offering light model in 3000k, high power factor and low THD.

Applications: commercial, residential, hospitality, entertainment and Hallways lighting.

#### **Fixture Information**

Size: 12W

Housing: Die-formed cold rolled steel Finish: Protective powder coat

Standard: Satin Nickel (SN)

Optional: Oil Rubbed Bronze (ORB)

Mounting: Standard: Wall Mount
Lens: High transmission acrylic

CRI: 90
Power Factor: .98
THD: <10%

120V Triac Dimming Type

(Min. Dimming Level 3%)

Voltage: Standard: 120V

Warranty: 10-Year Limited Warranty

## **Performance Data**

#### **Lumen Output:**

850 lm

#### Lumens Per Watt (typical):

70 lm/W

CCT:

3000K

Lifespan:

60,000 hrs

### Ratings & Certificates

ETL/cETL Listed CEC Listed
CEC Listed, Meets Title24 JA8 Requirements
JA10 Flicker Free
Damp Location Listed











# **Dimension**

Item	Depth	Width	Height
12W	4"	5.1"	14.5"







Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

# **Fixture Ordering Information**

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SMS-12-30-SN	12	850	3000	120V	Satin Nickel
LL-SMS-12-30-ORB	12	850	3000	120V	Oil Rubbed Bronze