

LL-KXTEU





Description

Die-Cast Aluminum Exit Sign

Illumination:

• Ultra bright, energy efficient, long life Red or Green LEDs.

Electrical:

• Dual 120/277 voltage.

• Charge rate/power "ON" LED indicator light and pushto-test switch for mandated code compliance testing.

• 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).

• Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.

• Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting:

• Aluminum mounting canopy included for top or end mount.

• Universal knockout pattern on back plate for wall mount.

Housing:

• Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).

- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

Options:

• SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

• 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.


- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

Warranty/Listing:

- Seven year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under Title 20 Regulations.



Dimensions:



LITELUME ©Lite Lume Corporation 2018 Page 1/2



www.litelume.com



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Model	No. of Faces		Letter Color		Housing Color		Face Panel		Battery		Options	
LL-KXTEU	1 2 3	Single Face Double Face Universal Single/ Double Face	R G	Red Green	W B A	White Black Aluminum	W B A	White Black Alumi- num	(blank) EM	AC-Only Battery Backup	SDT 2C TP USA	Self-Diagnostics ¹ Dual Circuit Operation ² Tamper-Proof Assembled In USA

¹ Available only with EM units. ² Available only with AC units.

LITELUME^{*} www.litelume.com ©Lite Lume Corporation 2018 833.LED.LUME