

# **Canopy Low Profile**







\*shown with Emergency Battery

#### **Description**

The LITELUME™ LED Canopy Low Profile Pack (LL-CLP) features a sealed die-cast construction and shatter-resistant polycarbonate acrylic optical lens with UV stabilizers. Compact in design and symmetry making this luminaire ideal for walkways, parking garages, entrance ways, and over-all canopy applications.

#### **Fixture Information**

Size: 27.74W/28.28W/39.56W/41.20W/

58.44W/59.50W

Housing: Die-cast Housing
Finish: Protective powdercoat

Color: Standard: Bronze

Custom Options:

Black (BK) White (WH)

Mounting: Sold separately
Lens: Polycarbonate
Surge Protector: Optional: 10 kVA

Standard: 120-277V Custom Option: 347-480V

Sensor: Standard: No sensor

Bi-level PIR motion sensor Remote battery back-up kit

Warranty: 10-Year Limited Warranty

### **Performance Data**

#### **Lumen Output:**

2,941 to 6,585 lm

## Lumens Per Watt (typical):

95.62 to 111.46 lm/W

CCT:

4000K 5000K

#### Distribution

Type V

#### Lifespan:

Features Philip Lumileds with up to 100,000 running

hours

#### **Ratings & Certificates**

UL Listed For Wet Location
DLC Qualified
IP66 rated






Voltage:



## **Dimension**

Item	Length	Height	Width	Weight
Canopy Low Profile	9.57"	9.57"	3.07"	10.10 lb






## Mounting

Standard mounting includes Pendant Mount or Direct Surface Mount.

### **Photometrics**

**Parking Garage** 





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

## **Fixture Ordering Information**

Item #	Part #	Wattage	Lumens	Kelvin	Voltage	Distribution	Custom Option Available*
4010	LL-CLP-28-50-UNV-BZ	28.28	3151	5000	120-277V	Type V	Yes
4011	LL-CLP-28-40-UNV-BZ	27.74	2941	4000	120-277V	Type V	Yes
4012	LL-CLP-42-50-UNV-BZ	39.56	4176	5000	120-277V	Type V	Yes
4013	LL-CLP-42-40-UNV-BZ	41.20	3939	4000	120-277V	Type V	Yes
4014	LL-CLP-58-50-UNV-BZ	59.50	6585	5000	120-277V	Type V	Yes
4015	LL-CLP-58-40-UNV-BZ	58.44	6535	4000	120-277V	Type V	Yes

<sup>\*</sup> Please contact LITELUME for all Custom Option Requests

## **Mounting Ordering Information**

Item #	Part #	Description
33	MS33	Bi-Level Pir Motion Sensor 33 ( *Must Select Lens Coverage Below* )
47	LW1	Lw1 Low Bay Coverage Lens
48	LS2	Ls2 High Bay Coverage Lens
21	RC21	Remote Control 21
43	C-EM-R-BZ	Remote Emergency Batter Back-Up Kit for Canopy 8W Bronze

<sup>\*</sup> Please contact LITELUME for all Custom Option Requests

## **Buy American Act Compliant Ordering Information**

Item #	Part #	Description
213	BAA-CLP	Buy American Act Compliant for Canopy Low Profile

<sup>\*</sup> Please contact LITELUME for all Custom Option Requests