



# Flood Light Large



## Description

The LITELUME™ Floodlight Large (LL-FLL) features a rugged, die-cast aluminum housing with a UV resistant powdercoat finish.

Applications: Billboard, Façade, Wall Washing and Landscape outdoor lighting.

## Fixture Information

Size:	135W/195W
Housing:	Die-cast Aluminum Housing
Finish:	Protective powdercoat
Color:	Standard: Bronze Custom Options: Black (BK) White (WH) Grey (BY)
Mounting:	Slip-fitter Trunnion Mount
Lens:	Polycarbonate
Surge Protector:	Optional: 10 kVA
Voltage:	Standard: 120-277V
Sensor:	Standard: No sensor Custom: Button Photocell (120-277V)
Warranty:	10-Year Limited Warranty

## Performance Data

### Lumen Output:

16,401 to 24,500 lm

### Lumens Per Watt (typical):

94 to 100 lm/W

### CCT:

4000K  
5000K

### Beam Angle:

107°

### Lifespan:

Features Cree Cob LED with up to 100,000 running hours

## Ratings & Certificates

UL Listed For Wet Location  
DLC Qualified  
IP66 rated







## Dimension

Item	Width	Length	Height
Floodlight Large w Slip-fitter	5.72"	17.78"	18.76"
Floodlight Large w Trunnion Mount	5.72"	17.78"	15.63"

### Slip Fitter



### Trunnion Mount



## Mounting Options




**Slip Fitter-** Die-cast aluminum slip-fitter mounts on 23/8" to 3" O.D. tenon easily.

**Trunnion Mount-** Die-cast aluminum trunnion is easily adapted to many surfaces and allows easy fixture aiming angles


## Photometrics

### 135W

#### Luminous Intensity Distribution Curve




#### Illuminance at a Distance




### 195W

#### Luminous Intensity Distribution Curve



#### Illuminance at a Distance





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

## Fixture Ordering Information

Item #	Part #	Wattage	Lumens	Kelvin	Voltage	Beam Angle	Custom Option Available*
3310	LL-FLL-135-50-UNV-BZ	135	16700	5000	120-277	107	Yes
3311	LL-FLL-135-40-UNV-BZ	135	16401	4000	120-277	107	Yes
3313	LL-FLL-195-50-UNV-BZ	195	24500	5000	120-277	107	Yes
3314	LL-FLL-195-40-UNV-BZ	195	24000	4000	120-277	107	Yes

\* Please contact LITELUME for all Custom Option Requests

## Mounting Ordering Information

Item #	Part #	Description
53	FLM/FLL-SF	SLIP-FITTER ( FLM & FLL )
54	FLM/FLL-TR	TRUNION MOUNT ( FLM & FLL )

\* Please contact LITELUME for all Custom Option Requests

## Accessories Ordering Information

Item #	Part #	Wattage
23	PC	BUTTON PHOTOCELL, 120-277V
	SUB"UNV" WITH "480"	480 Volt

\* Please contact LITELUME for all Custom Option Requests

## Buy American Act Compliant Ordering Information

Item #	Part #	Description
206	BAA-FLL	Buy America Act Compliant For Floodlight Large

\* Please contact LITELUME for all Custom Option Requests