



Post Top Area Light Medium



Description

The LITELUME™ Post Top Area Light Medium Luminaire (LL-PTALM) combines style with performance. Featuring a die-cast aluminum housing with outstanding corrosion protection, and secondary UV resistant polycarbonate optics. The PTALM provides an aesthetically pleasing addition to any walkway, park, downtown corridor or parking lot with its steady well-defined construction. The highly functioning optics provide maximum distribution to make the PTALM a premier choice for outdoor area lighting.

Fixture Information

| | |
|------------------|---|
| Size: | 50W/98W |
| Housing: | Die-cast aluminum housing |
| Finish: | Protective powdercoat |
| Color: | Standard: Bronze Custom Options: Black (BK), White (WH) and Gray (GY) |
| Mounting: | Tenon fits 2 3/8" standard OD |
| Power Factor: | >.95 |
| Driver: | Meanwell HLG |
| Lens: | Polycarbonate |
| Surge Protector: | Standard: 4kVA Optional: 10kVA, 20kVA |
| Voltage: | Standard: 120-277V Custom Option: 347-480V |
| Sensor: | Standard: No sensor |
| Warranty: | 10-Year Limited Warranty |

Performance Data

Lumen Output:

5878 to 12577 lm

Lumens Per Watt (typical):

117.56 to 128.33 lm/W

CCT:

3000K
4000K
5000K

Distribution:

Type V

Lifespan:

Features Philips Lumileds with up to 100,000 running hours.

Ratings & Certificates


ETL Listed for Wet Location






Dimensions

| Item | Width | Length | Height |
|---------------------------|-------|--------|--------|
| Post Top Area Light Small | 9.45" | 13.85" | 17.19" |




Photometric Data

47W



101W





| | |
|--------------|--|
| Project Name | |
| Catalog # | |
| Job Type | |
| Prepared By | |
| Notes | |

Fixture Ordering Information

| Item # | Part # | Wattage | Lumens | Kelvin | Voltage | Type Distribution | Custom Option Available* |
|--------|--------------------------|---------|--------|--------|---------|-------------------|--------------------------|
| 1350 | LL-PTALM-45-50-UNV-T3-BZ | 50 | 6121 | 5000 | 120-277 | T3 | Yes |
| 1351 | LL-PTALM-45-40-UNV-T3-BZ | 50 | 5998 | 4000 | 120-277 | T3 | Yes |
| 1352 | LL-PTALM-45-30-UNV-T3-BZ | 50 | 5878 | 3000 | 120-277 | T3 | Yes |
| 1360 | LL-PTALM-45-50-UNV-T5-BZ | 50 | 6121 | 5000 | 120-277 | T5 | Yes |
| 1361 | LL-PTALM-45-40-UNV-T5-BZ | 50 | 5998 | 4000 | 120-277 | T5 | Yes |
| 1362 | LL-PTALM-45-30-UNV-T5-BZ | 50 | 5878 | 3000 | 120-277 | T5 | Yes |
| 1370 | LL-PTALM-95-50-UNV-T3-BZ | 98 | 12577 | 5000 | 120-277 | T3 | Yes |
| 1371 | LL-PTALM-95-40-UNV-T3-BZ | 98 | 12325 | 4000 | 120-277 | T3 | Yes |
| 1372 | LL-PTALM-95-30-UNV-T3-BZ | 98 | 12078 | 3000 | 120-277 | T3 | Yes |
| 1380 | LL-PTALM-95-50-UNV-T5-BZ | 98 | 12577 | 5000 | 120-277 | T5 | Yes |
| 1381 | LL-PTALM-95-40-UNV-T5-BZ | 98 | 12325 | 4000 | 120-277 | T5 | Yes |
| 1382 | LL-PTALM-95-30-UNV-T5-BZ | 98 | 12078 | 3000 | 120-277 | T5 | Yes |

* Please contact LITELUME for all Custom Option Requests

Accessories Ordering Information

| Item # | Part # | Wattage |
|--------|----------------------|--|
| 22 | TLPC | Twist Lock Photocell and Receptacle 120-277V |
| 24 | TLPC480 | Twist Lock Photocell and Receptacle 480V |
| 331 | NWTL111 | Wattstopper NWTL-111 Built-in Wireless Control Node |
| 332 | WNM | Wattstopper Wireless Network Manager For NWTL-111 Built-in Wireless Control Node |
| 333 | ECM20ZB | EU Controls Zigbee Lighting And Photo Control |
| 334 | DIM-4 | Sun-Tech Dimulator 120-277V |
| 335 | DIM-4-HV | Sun-Tech Dimulator 480V |
| 340 | SP10 | 10kVA Surge Protector |
| 341 | SP20 | 20kVA Surge Protector |
| 342 | R3 | Twist Lock Receptacle 3 Pin |
| 343 | R7 | Twist Lock Receptacle 7 Pin |
| 480 | SUB "UNV" WITH "480" | 480 VOLT |

* Please contact LITELUME for all Custom Option Requests

Buy American Act Compliant Ordering Information

| Item # | Part # | Description |
|--------|-----------|---|
| 229 | BAA-PTALM | Buy American Act Compliant for Post Top Area Light Medium |

* Please contact LITELUME for all Custom Option Requests